

ENGINE POWERED

LED TECHNOLOGY

2200 sqm
Illuminated area

**built-in
toilette**

162h
running time

**designed and created
for your needs**

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

X-TR

2X150W LED - 8M



**more sustainable
and environmentally
friendly future**

TRIME[®]
Lighting Towers

X-TR

2X150W LED - 8M

LED TECHNOLOGY

2200 sqm
Illuminated area

RUNNING TIME

81 litres tank
162h
Low fuel consumption

Save
money



MINIMAL
service



APPLICATIONS



Constructions



Parking area

Emergency



Events



Military applications

FEATURES

- ✓ Built-in toilette
- ✓ Built-in 6kVA Single-phase generator
- ✓ Fresh water level gauge
- ✓ Waste water level gauge
- ✓ Bathroom light
- ✓ Technical room light
- ✓ Telescopic ladder for floodlights regulation
- ✓ Road trailer
- ✓ Removable ladder for easy and safe bathroom entrance
- ✓ 4 sides lifting eyes
- ✓ 2 Multi-directionally adjustable and tiltable by hands floodlights
- ✓ 8mt hydraulic vertical telescopic mast
- ✓ Galvanized metalworks
- ✓ 80 µm powder coating
- ✓ Forklift pockets for effective handling
- ✓ Guided main coiled cable to avoid damage during tower operation
- ✓ 4 drop down stabilizers

ENGINE POWERED



Dimensions & weight

Dimensions min (mm)	3446x2268x3054 (LxWxH)
Dimensions max (mm)	3446x2268x8000 (LxWxH)
Total weight (kg)	1770

Floodlights

Type	Led
Power (each)	150W
Floodlights number	2
IP level	65
Illuminated area (sqm)	2200

Mast

Lifting method	Hydraulic
Max Height	8 m
Max Wind Speed	110 km/h

Generator

Model	Synchronous
Frequency (Hz)	50
Rated Output	6 kVA
Rated voltage	230V

Engine

Model	Kohler KD 15/440
Cylinders	1
Fuel	Diesel
r.p.m.	3000
Fuel tank (l)	81
Consumption (l/h)	0,55
Running time	162 h
Start	Electric
Oil sump capacity (l)	1,5
Displacement cm ³	442
Cooling system	air

Water

Waste water tank capacity (l)	95
Fresh water tank capacity (l)	95
Cold water	yes
Capacity (l)	36
Recirculating flush tank (l)	160



4 units per truck

Safe packaging and loading
allowing quick unloading



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.